

UNITED

LABORATORIES

- Distilled from organic plant material.
- Contains no petroleum distillates.
- Contains no chlorinated hydrocarbons.
- Starves dragonflies and pests by eliminating their food source.
- Non-caustic.
- Non-corrosive.

GENERAL INFORMATION:

Slime and Grease Cutter contains a high percentage of cold pressed fresh-smelling citrus oils, which are natural degreasers that are ideal for wastewater treatment facilities.

COLLECTION SYSTEM:

LIFT STATIONS — Mix 1 part of **Slime and Grease Cutter** with 30 parts of water and spray on sidewalls. **Slime and Grease Cutter's** superior emulsification system solubilizes and cuts oil, grease, scum and slime build-up off the walls, so it can be easily flushed away.

For a product which layers the top of the lift station and stays there working, there's United 493 Lift Station Maintainer.

WASTEWATER TREATMENT PLANTS:

"CHOCOLATE FOAM" Controllant: For hand sprayed application, mix 1 part of **Slime and Grease Cutter** with 10 parts of water. The A176 Chapin sprayer equipped with a fan tip (A180) is recommended. Apply the diluted product directly to foam for immediate knock-down.

For application by automatic jet-spray system, mix 1 part of **Slime and Grease Cutter** with 30 parts of water. Apply the diluted product directly to the foam for immediate knock-down.

Use United 53 Defoamer to knock down detergent foam.

When using a metering pump with this product, you must use Viton® tubing.

United 594

Slime and Grease Cutter

KEEP OUT OF REACH OF CHILDREN.

CAUTION

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

PRECAUCION AL USARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

Manufactured and Sold Exclusively By:
UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

CAUTION:

Contains d-1, 8 (9)-p-menthadiene (CAS# 5989-27-5). Harmful if swallowed. Avoid eye and skin contact. **Slime and Grease Cutter** is combustible and should be stored in a cool place, away from exposure to heat and open flames. Rags soaked with **Slime and Grease Cutter** may spontaneously combust. To avoid this danger, used rags should be soaked with water and/or stored in a container full of soapy water.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Immediately flush with plenty of water for at least 15 minutes. Get prompt medical attention.

SKIN: Wash with soap and plenty of water. If symptoms develop, seek medical attention.

INHALATION: Remove to fresh air. If symptoms develop, seek medical attention. If not breathing, give artificial respiration.

INGESTION: DO NOT induce vomiting. Get medical attention immediately. If vomiting occurs, have victim lean forward to reduce risk of aspiration.

An MSDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the MSDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

HMIS® III CODE: 0=MINIMAL 1=SLIGHT 2=MODERATE 3=SERIOUS 4=SEVERE PERSONAL PROTECTION INDEX: Glasses and Gloves	HEALTH	2
	FLAMMABILITY	2
	PHYSICAL HAZARD	0
	PERSONAL PROTECTION	B