



UNITED

LABORATORIES

United 846 FOG-Away Pretreatment for Wastewater is a specially formulated blend of microbes developed to completely degrade grease in wastewater pre-treatment, collection system, equalization tank and headworks applications. **FOG-Away Pretreatment for Wastewater** will bio-degrade grease in mains, lift stations, equalization tanks and at the headworks at a waste water plant without mobilizing the grease. This reduces excessive Jetting of the lines and other related infrastructure significantly. **FOG-Away Pretreatment for Wastewater** is also effective in reducing line grease build-up.

The unique formulation of **United 846 FOG-Away Pretreatment for Wastewater**:

- Includes Promicrobials capable of fast degradation of Fats, Oils, and Grease (FOG).
- Has a pH range of as low as 5.0 to as high as 9.8.
- Works with an effective temperature range of 38° – 145°F and an optimal temperature range of 60° – 90°F.
- Maintains optimal FOG degradation through three-fold action:
 1. Uses patented strains of gram-positive bacteria to bio-degrade long-chain fatty acids.
 2. Promicrobials advance fast degradation of FOG.
 3. Specific nutrients and microbial enhancers encourage accelerated bacterial activity.
- Passes the EPA Methods 1664 and 1664A, proving that grease is not mobilized and allowed to pass through the mains into and through the wastewater plant.
- Improves line inspection results by reducing the FOG in the mains which, in turn, reduces FOG accumulation in the wastewater plant.
- Reduces odors that can lead to complaints generated from the public.

United 846

FOG-Away Pretreatment for Wastewater

**KEEP OUT OF REACH OF CHILDREN.
CAUTION
SEE SIDE PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS.**

PRECAUCION AL USARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

**Manufactured and Sold Exclusively By:
UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com**

DIRECTIONS FOR USE:

Treatment of Mains:

Inject, meter or drip **FOG-Away Pretreatment for Wastewater** into mains up stream, starting 7 - 10 manholes above the grease point sources.

Dosage rates:

Low to moderate flow: 10 – 20 oz. per day.

High volume flows: Dilute at a rate from 1:10,000 to 1:50,000 parts per day, adjusting the dilution rate based on results. Call your United Representative for technical support.

Treatment for headworks and Equalization Tanks:

Low to Moderate flow: 10 – 20 oz. per day.

For higher flow rates use at 1:10,000 – 1:20,000 parts per day.

Note:

In equalization tanks the retention time may require more, or less product. Consult your United Representative.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush with plenty of water for at least 15 minutes and call a physician or poison control center.

SKIN: Wash with soap and water. If irritation persists, call a physician or poison control center.

INHALATION: Not applicable.

INGESTION: Rinse mouth and throat. Give two glasses of water to dilute product. DO NOT induce vomiting. Call a physician or poison control center.

An MSDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the MSDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

HMIS® III CODE: 0=MINIMAL 1=SLIGHT 2=MODERATE 3=SERIOUS 4=SEVERE PERSONAL PROTECTION INDEX: Glasses	HEALTH	1
	FLAMMABILITY	0
	PHYSICAL HAZARD	0
	PERSONAL PROTECTION	A